


Adapters Between Series—Non-Locking G874 to:


BNC Jack



Delta P/N **2234-000-N000-31**

Length: 1.66
Nominal Impedance: 50Ω
Frequency Range: DC-4.0 GHz
Operating Voltage: 500 max.


BNC Plug



Delta P/N **2234-000-N000-14**

Length: 1.81
Nominal Impedance: 50Ω
Frequency Range: DC-4.0 GHz
Operating Voltage: 500 max.


C Jack



Delta P/N **2234-000-N000-32**

Length: 1.91
Nominal Impedance: 50Ω
Frequency Range: DC-8.5 GHz
Operating Voltage: 1000 max.


C Plug



Delta P/N **2234-000-N000-33**

Length: 2.05
Nominal Impedance: 50Ω
Frequency Range: DC-8.5 GHz
Operating Voltage: 1000 max.


HN Jack



Delta P/N **2234-000-N000-36**

Length: 1.88
Nominal Impedance: 50Ω
Frequency Range: DC-8.5 GHz
Operating Voltage: 1500 max.


HN Plug



Delta P/N **2234-000-N000-37**

Length: 2.28
Nominal Impedance: 50Ω
Frequency Range: DC-8.5 GHz
Operating Voltage: 1500 max.


N Jack



Delta P/N **2234-000-N000-18**

Length: 1.63
Nominal Impedance: 50Ω
Frequency Range: DC-8.5 GHz
Operating Voltage: 1000 max.


N Plug



Delta P/N **2234-000-N000-17**

Length: 2.01
Nominal Impedance: 50Ω
Frequency Range: DC-8.5 GHz
Operating Voltage: 1000 max.


SC Jack



Delta P/N **2234-000-N000-51**

Length: 1.91
Nominal Impedance: 50Ω
Frequency Range: DC-8.5 GHz
Operating Voltage: 1000 max.


SC Plug



Delta P/N **2234-000-N000-52**

Length: 2.05
Nominal Impedance: 50Ω
Frequency Range: DC-8.5 GHz
Operating Voltage: 1000 max.


SMA Jack



Delta P/N **2234-000-N000-41**

Length: 1.68
Nominal Impedance: 50Ω
Frequency Range: DC-8.5 GHz
Operating Voltage: 335 max.


SMA Plug



Delta P/N **2234-000-N000-42**

Length: 1.84
Nominal Impedance: 50Ω
Frequency Range: DC-8.5 GHz
Operating Voltage: 335 max.

TNC Jack



Delta P/N **2234-000-N000-23**

Length: 1.66
Nominal Impedance: 50Ω
Frequency Range: DC-8.5 GHz
Operating Voltage: 500 max.

TNC Plug



Delta P/N **2234-000-N000-45**

Length: 1.87
Nominal Impedance: 50Ω
Frequency Range: DC-8.5 GHz
Operating Voltage: 500 max.


UHF Jack



Delta P/N **2234-000-N000-48**

Length: 1.80
Nominal Impedance: Nonconstant
Frequency Range: UHF Range
Operating Voltage: 500 max.

UHF Plug



Delta P/N **2234-000-N000-29**

Length: 2.06
Nominal Impedance: Nonconstant
Frequency Range: UHF Range
Operating Voltage: 500 max.