


Adapters Between Series—Locking G874 to:


BNC Jack



Delta P/N **2234-000-N000-15**

Length: 1.66
Nominal Impedance: 50Ω
Frequency Range: DC-4.0 GHz
Operating Voltage: 500 max.


BNC Plug



Delta P/N **2234-000-N000-30**

Length: 1.81
Nominal Impedance: 50Ω
Frequency Range: DC-4.0 GHz
Operating Voltage: 500 max.


C Jack



Delta P/N **2234-000-N000-34**

Length: 1.91
Nominal Impedance: 50Ω
Frequency Range: DC-8.5 GHz
Operating Voltage: 1000 max.


C Plug



Delta P/N **2234-000-N000-35**

Length: 2.05
Nominal Impedance: 50Ω
Frequency Range: DC-8.5 GHz
Operating Voltage: 1000 max.


HN Jack



Delta P/N **2234-000-N000-38**

Length: 1.88
Nominal Impedance: 50Ω
Frequency Range: DC-8.5 GHz
Operating Voltage: 1500 max.


HN Plug



Delta P/N **2234-000-N000-39**

Length: 2.28
Nominal Impedance: 50Ω
Frequency Range: DC-8.5 GHz
Operating Voltage: 1500 max.


N Jack



Delta P/N **2234-000-N000-40**

Length: 1.63
Nominal Impedance: 50Ω
Frequency Range: DC-8.5 GHz
Operating Voltage: 1000 max.


N Plug



Delta P/N **2234-000-N000-24**

Length: 2.01
Nominal Impedance: 50Ω
Frequency Range: DC-8.5 GHz
Operating Voltage: 1000 max.


SC Jack



Delta P/N **2234-000-N000-53**

Length: 2.07
Nominal Impedance: 50Ω
Frequency Range: DC-8.5 GHz
Operating Voltage: 1000 max.


SC Plug



Delta P/N **2234-000-N000-54**

Length: 2.05
Nominal Impedance: 50Ω
Frequency Range: DC-8.5 GHz
Operating Voltage: 1000 max.


SMA Jack



Delta P/N **2234-000-N000-43**

Length: 1.68
Nominal Impedance: 50Ω
Frequency Range: DC-8.5 GHz
Operating Voltage: 335 max.


SMA Plug



Delta P/N **2234-000-N000-44**

Length: 1.84
Nominal Impedance: 50Ω
Frequency Range: DC-8.5 GHz
Operating Voltage: 335 max.


TNC Jack



Delta P/N **2234-000-N000-46**

Length: 1.66
Nominal Impedance: 50Ω
Frequency Range: DC-8.5 GHz
Operating Voltage: 500 max.


TNC Plug



Delta P/N **2234-000-N000-47**

Length: 1.87
Nominal Impedance: 50Ω
Frequency Range: DC-8.5 GHz
Operating Voltage: 500 max.


UHF Jack



Delta P/N **2234-000-N000-49**

Length: 1.80
Nominal Impedance: Nonconstant
Frequency Range: UHF Range
Operating Voltage: 500 max.

UHF Plug



Delta P/N **2234-000-N000-50**

Length: 2.06
Nominal Impedance: Nonconstant
Frequency Range: UHF Range
Operating Voltage: 500 max.