



OUTLINE

NOTES:

1. ASSEMBLED CONNECTOR INTERFACE IS DESIGNED IN ACCORDANCE WITH MIL-STD-348.

2. MATERIAL: BODY - CORROSION RESISTANT STEEL PER ASTM B582

CONTACT - BRASS PER ASTM B16 INSULATOR - TEFLON PER ASTM D1710 GASKET - SILICONE RUBBER PER ZZ-R-765

UNLESS OTHERWISE SPECIFIED: TOLERANCES: 3 PLACES = ±.005, 2 PLACES = ±.02, ANGLES = ±1/2', SURFACE FINISH = 63

3. FINISHES: CONTACT - GOLD PLATE PER MIL-G-45204

ALL OTHER METAL PARTS - NICKEL PLATE PER QQ-N-290

| | DELTA | ELECTRONIC | S MFG. C | ORP. Bev | verly, MA 01915 |
|----------------|---------------------------|--------------|-----------------------|-----------------|--------------------------------|
| | TITLE: | | | | |
| | "PUSH- | -ON"BNC | PLUG | TO BNC | JACK ADAPTER |
| | 4 | | | | |
| 6/9/05 | Drawn by | Scale | Ckd. by | Engr Appd | FILE NAME: |
| 6/9/05 DATE | Drawn by BJM 6/9/05 | Scale 2/1 | Ckd. by M R | Engr Appd MR | FILE NAME: 2234000K001-170T |

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF DELTA ELECTRONICS MFG CORP. AND SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT THEIR EXPRESS WRITTEN CONSENT.