


Product Area	Female socket IP 67 Push-Pull connectors	serie 430	Pole Article number	5 09 4916 015 05
--------------	---	-----------	---------------------	---------------------


**illustration**



**scale drawing**



**Contact Arrangement**



You can find the item description and assembly instruction on the next page.

**Technical data**

**Common values**

Connector Design	Female socket
Connector locking system	Push-Pull locking
Termination	solder
Wire gauge (mm)	0,25 mm <sup>2</sup>
Wire gauge (AWG)	24
Cable outlet	-
Upper temperature	+85 °C
Lower temperature	-40 °C

**Material**

Material of contact	CuSn (bronze)
Contact plating	Au (gold)
Material of contact body	PBT, PA
Material of housing	CUZn (brass nickel plated)

**Cable data**

material housing	-
insulation single lead	-
single lead structure	-
conductor resistance	-

**Electrical values**

Rated voltage	125 V
Rated impulse voltage	1500 V
Pollution degree	2
Overvoltage category	I
Material group	II
Rated current (40°C)	3 A
Volume resistivity	≤ 5 mΩ
EMV compliance	shieldable
Degree of protection	IP 67
Mechanical operation	>500 mating cycles

Contacts 5, Female socket IP 67




Product Area Female socket IP 67  
Push-Pull connectors

serie 430

Pole 5  
Article number 09 4916 015 05

Date: 2014-07-20 - Page 2 of 2

Item description



Installation instructions / Mounting cutout

