


Product Area	Kabelstecker, PROFIBUS M12 connectors B-Coding	serie 766	Pole	2
			Article number	77 4329 0000 60702 1000


#### illustration



#### scale drawing



#### Contact Arrangement



- 1 braun/brown
- 2 weiß/white
- 5 gelb/grün/yellow/greer

### Technical data

#### Common values

Connector Design	Male cable connector
Termination	crimp, overmoulded on cable
Wire gauge (mm)	0,25 mm <sup>2</sup>
Wire gauge (AWG)	22
Max. Cable outlet	-
Upper temperature	+85 °C
Lower temperature	-25 °C

#### Electrical values

Rated voltage	250 V
Rated impulse voltage	2500 V
Pollution degree	3
Overvoltage category	II
Material group	II
Rated current (40°C)	4 A
Volume resistivity	≤ 3 mΩ
Degree of protection	IP 67
Mechanical operation	>500 mating cycles

#### Material

Material of contact	CuZn (brass)
Contact plating	Au (gold)
Material of contact body	PUR
Material of housing	PUR

#### Cable data

material housing	PUR
single lead structure	19 × 0,127 mm
cable sheath Ø	7.8

Kabellänge: 10 m, Polzahl: 2, Kabelstecker  
PROFIBUS