


Product Area Female angled connector moulded, UL approved
M12 connectors A-Coding serie 763

Pole 5
Article number 78 3444 35 05


illustration



scale drawing



Contact Arrangement



- 1 braun
- 2 weiß
- 3 blau
- 4 schwarz
- 5 grau

Technical data

Common values

Connector Design	Female angled cable connector
Connector locking system	Screw-locking
Termination	crimp, overmoulded on cable
Wire gauge (mm)	0,25 mm ²
Wire gauge (AWG)	24
Upper temperature	+85 °C
Lower temperature	-25 °C

Electrical values

Rated voltage	125 V
Rated impulse voltage	1500 V
Pollution degree	3
Overvoltage category	II
Material group	II
Rated current (40°C)	4 A
Volume resistivity	≤ 3 mΩ
Degree of protection	IP 68
Mechanical operation	>100 mating cycles

Material

Material of contact	CuSn (bronze)
Contact plating	Au (gold)
Material of contact body	PUR
Material of housing	PUR

Cable data

material housing	PUR
insulation single lead	SR-PVC
single lead structure	42 x 0,1
cable sheath Ø	5.1
approval	UL

Contacts 5: Cable lenght 5 m, cable 5 x 0,25
PUR, female angled connector moulded, UL
approved