


Product Area	Female cable connector moulded, Stainless steel ring nut M12 connectors A-Coding serie 763	Pole	3
		Article number	79 3430 55 04


illustration




scale drawing



Contact Arrangement



Attenuation characteristic



Technical data

Common values	
Connector Design	Female cable connector
Connector locking system	Screw
Termination	crimp, overmoulded on cable
Wire gauge (mm)	0,34 mm ²
Wire gauge (AWG)	22
Upper temperature	+85 °C
Lower temperature	-25 °C

Material	
Material of contact	CuSn (bronze)
Contact plating	Au (gold)
Material of contact body	PUR
Material of housing	PUR

Electrical values	
Rated voltage	250 V
Rated impulse voltage	2500 V
Pollution degree	3
Overvoltage category	II
Material group	II
Rated current (40°C)	4 A
Volume resistivity	≤ 3 mΩ
Degree of protection	IP 68
Mechanical operation	>100 mating cycles

Cable data	
material housing	PUR
insulation single lead	PVC
single lead structure	42 x 0,1
cable sheath Ø	5
conductor resistance	55Ω/Km
temperature range cable movable c from	-5
temperature range cable movable c to	70
temperature range cable fixed c from	-25
temperature range cable fixed c to	70
bending radius cable fixed	25 mm
bending radius cable movable	50 mm

Contacts 4: Cable lenght 5 m, cable 4 x 0,34 PUR, female cable connector moulded, stainless steel ring nut

