


Product Area	Male cable connector moulded M12 connectors B-Coding	serie 766	Pole Article number	4 79 4429 50 04
--------------	---	-----------	---------------------	--------------------


illustration



scale drawing



Contact Arrangement



Technical data

Common values

Connector Design	Male cable connector
Connector locking system	Screw
Termination	crimp, overmoulded on cable
Wire gauge (mm)	0,50 mm <sup>2</sup>
Wire gauge (AWG)	20
Upper temperature	+85 °C
Lower temperature	-25 °C

Electrical values

Rated voltage	250 V
Rated impulse voltage	2500 V
Pollution degree	3
Overvoltage category	II
Material group	II
Rated current (40°C)	4 A
Volume resistivity	≤ 3 mΩ
EMV compliance	not shielded
Degree of protection	IP 68
Mechanical operation	>100 mating cycles

Material

Material of contact	CuZn (brass)
Contact plating	Au (gold)
Material of contact body	PUR
Material of housing	PUR

Cable data

material housing	PUR
insulation single lead	PVC
single lead structure	63 x 0,1 mm
cable sheath Ø	5.7
conductor resistance	39 Ω/Km
temperature range cable movable c from	-5
temperature range cable movable c to	70
temperature range cable fixed c from	-25
temperature range cable fixed c to	70
bending radius cable fixed	28 mm
bending radius cable movable	45 mm
cable diameter	5.7



Cable: 4 x 0,5 mm<sup>2</sup>, contacts: 4, male cable connector moulded, cable length 5 m