


Product Area	Male connector M12 x 1 – female angled connector with LED PNP NOC M12 x 1 Connecting cables - sensor connectors serie 765	Pole	4
		Article number	79 5004 10 04


Belegungspläne



illustration




scale drawing




Contact Arrangement

Stifteinsatz M12
Male insert M12



Bucheneinsatz M12
Female insert M12



- 1 braun/brown
- 2 weiß/white
- 3 blau/blue
- 4 schwarz/black

Technical data

Common values

Connector Design	Male cable connector- female angled connector
Connector locking system	Screw
Termination	crimp, overmoulded on cable
Wire gauge (mm)	0,34 mm ²
Wire gauge (AWG)	22
Upper temperature	+85 °C
Lower temperature	-25 °C

Material

Material of contact	Stift/ CuZn brass), socket/ CuSn (bronze)
Contact plating	Au (gold)
Material of contact body	PUR
Material of housing	PUR

Cable data

Contacts 4: Cable length 1 m, Male connector M12 x 1 – female angled connector with LED PNP NOC M12 x 1, cable 4 x 0,34 PUR

Electrical values

Rated voltage	30 V
Rated impulse voltage	500 V
Pollution degree	3
Overvoltage category	II
Material group	II
Rated current (40 °C)	4 A
Volume resistivity	≤ 3 mΩ
Degree of protection	IP 68
Mechanical operation	>100 mating cycles

