


Product Area Female cable duo connector, plastic locking system, screw termination
M12 connectors A-Coding serie 713

Pole 5
Article number 99 0436 142 05


illustration



scale drawing



Contact Arrangement



	X	Y
1	-2,50	0,00
2	0,00	2,50
3	2,50	0,00
4	0,00	-2,50
5	0,00	0,00

You can find the item description and assembly instruction on the next page.

Technical data

Common values

Connector Design	Female cable connector
Connector locking system	Screw
Termination	screw
Wire gauge (mm)	0,75 mm ²
Wire gauge (AWG)	18
Upper temperature	+85 °C
Lower temperature	-40 °C

Material

Material of contact	CuZn (brass)
Contact plating	CuSnZn (Optalloy)
Material of contact body	PA
Material of housing	PA

Cable data

Contacts 5: Female cable duo connector, plastic locking system, screw termination, 2 cables: Ø 2,1 – 3 mm or Ø 4 – 5 mm

Electrical values


Rated voltage	125 V
Rated impulse voltage	1500 V
Pollution degree	3
Overvoltage category	II
Material group	III
Rated current (40°C)	4 A
Volume resistivity	≤ 8 mΩ
Degree of protection	IP 67
Mechanical operation	> 50 mating cycles



Product Area Female cable duo connector, plastic locking system, screw termination
M12 connectors A-Coding serie 713

Pole 5
Article number 99 0436 142 05

Item description



Installation instructions / Mounting cutout

