


Product Area Male cable connector, shieldable, screw termination, shielding ring, stainless steel version
M12 connectors A-Coding serie 713

Pole 5
Article number 99 1437 992 05

illustration



scale drawing




Contact Arrangement



	X	Y
1	2,50	0,00
2	0,00	2,50
3	-2,50	0,00
4	0,00	-2,50
5	0,00	0,00

Attenuation characteristic



You can find the assembly instruction on the next page.

Technical data

Common values

Connector Design	Male cable connector
Connector locking system	Screw
Termination	screw
Wire gauge (mm)	0,75 mm ²
Wire gauge (AWG)	18
Cable outlet	6 - 8 mm
Upper temperature	+85 °C
Lower temperature	-40 °C

Material


Material of contact	CuZn (brass)
Contact plating	Au (gold)
Material of contact body	PA
Material of housing	stainless steel 1.4404

Cable data

Contacts 5: cable outlet: 6-8 mm, Male cable connector, shieldable, screw termination, shielding ring, stainless steel version

Electrical values

Rated voltage	125 V
Rated impulse voltage	1500 V
Pollution degree	3
Overvoltage category	II
Material group	II
Rated current (40°C)	4 A
Volume resistivity	≤ 3 mΩ
Degree of protection	IP 67
Mechanical operation	>100 mating cycles



Product Male cable connector, shieldable, screw termination, shielding ring, stainless steel version
Area M12 connectors A-Coding serie 713

Pole 5
Article number 99 1437 992 05

Date: 2014-07-20 - Page 2 of 2

Installation instructions / Mounting cutout

