


| | | | |
|--------------|--|----------------|---------------|
| Product Area | Male cable connector with cable clamp, cable outlet 4-6 mm M16 connectors IP 40 | Pole | 2 |
| | serie 581 | Article number | 99 2001 10 02 |


illustration



scale drawing



Contact Arrangement



| | X | Y |
|---|-------|------|
| 1 | 3,50 | 0,00 |
| 2 | -3,50 | 0,00 |

Attenuation characteristic



You can find the item description on the next page.

Technical data

Common values

| | |
|--------------------------|----------------------|
| Connector Design | Male cable connector |
| Connector locking system | Screw |
| Termination | solder |
| Wire gauge (mm) | 0,75 mm ² |
| Wire gauge (AWG) | 20 |
| Cable outlet | 4 - 6 mm |
| Upper temperature | +85 °C |
| Lower temperature | -40 °C |

Material


| | |
|--------------------------|----------------------------|
| Material of contact | CuZn (brass) |
| Contact plating | Ag (silver) |
| Material of contact body | PBT (UL 94 V-0) |
| Material of housing | CUZn (brass nickel plated) |

Cable data

Contacts 2, male cable connector with cable clamp, shieldable, cable outlet 4 - 6 mm, silver plated contacts

Electrical values

| | |
|-----------------------|--------------------|
| Rated voltage | 250 V |
| Rated impulse voltage | 1500 V |
| Pollution degree | 1 |
| Overvoltage category | I |
| Material group | III |
| Rated current (40°C) | 7 A |
| Volume resistivity | ≤ 5 mΩ |
| EMV compliance | shielded |
| Degree of protection | IP 40 |
| Mechanical operation | >500 mating cycles |



Product Male cable connector with cable clamp, cable outlet 4-6 mm
Area M16 connectors IP 40 serie 581

Pole 2
Article number 99 2001 10 02

Date: 2014-07-20 - Page 2 of 2

Item description

