


Product Male cable connector with cable clamp, cable outlet 6-8 mm  
Area M16 connectors IP 40 serie 581

Pole 2  
Article number 99 2001 29 02


#### illustration



#### scale drawing




#### Contact Arrangement



	X	Y
1	3,50	0,00
2	-3,50	0,00

#### Attenuation characteristic



You can find the item description on the next page.

#### Technical data

##### Common values

Connector Design	Male cable connector
Connector locking system	Screw
Termination	solder
Wire gauge (mm)	0,75 mm <sup>2</sup>
Wire gauge (AWG)	20
Cable outlet	6 - 7,8 mm
Upper temperature	+85 °C
Lower temperature	-40 °C

##### Material

Material of contact	CuZn (brass)
Contact plating	Au (gold)
Material of contact body	PBT (UL 94 V-0)
Material of housing	CUZn (brass nickel plated)

##### Cable data

Contacts 2, male cable connector with cable clamp, shieldable, cable outlet 6 - 8 mm, gold plated contacts

##### Electrical values

Rated voltage	250 V
Rated impulse voltage	1500 V
Pollution degree	I
Overvoltage category	I
Material group	III
Rated current (40°C)	7 A
Volume resistivity	≤ 3 mΩ
EMV compliance	shielded
Degree of protection	IP 40
Mechanical operation	>500 mating cycles



Product Male cable connector with cable clamp, cable outlet 6-8 mm  
 Area M16 connectors IP 40 serie 581

Pole 2  
 Article number 99 2001 29 02

Date: 2014-07-20 - Page 2 of 2

Item description

