


Product	Female cable connector with cable connector, screw terminal connection, shieldable, cable gland 4-6 mm	Pole	3 DIN
Area	M16 connectors IP 40	serie 581	Article number 99 2006 210 03


illustration



scale drawing



Contact Arrangement



	X	Y
1	-3,50	0,00
2	0,00	3,50
3	3,50	0,00

Attenuation characteristic



You can find the item description on the next page.

Technical data

Common values

Connector Design	Female cable connector
Termination	screw
Wire gauge (mm)	0.25 - 1.5 mm ²
Wire gauge (AWG)	24 - 16
Cable outlet	4 - 6 mm
Upper temperature	+85 °C
Lower temperature	-40 °C

Material


Material of contact	CuSn (bronze)
Contact plating	Ag (silver)
Material of contact body	PBT (UL 94 V-0)
Material of housing	CUZn (brass nickel plated)

Cable data

Number of pins: 3 DIN, female cable connector with cable clamp, screw terminal connection, shieldable, cable gland 4 - 6 mm, silver contacts

Electrical values

Rated voltage	250 V
Rated impulse voltage	1500 V
Pollution degree	I
Overvoltage category	I
Material group	III
Rated current (40°C)	7 A
Volume resistivity	≤ 5 mΩ
Degree of protection	IP 40
Mechanical operation	>500 mating cycles



Product	Female cable connector with cable connector, screw terminal connection, shieldable, cable gland 4-6 mm	Pole	3 DIN
Area	M16 connectors IP 40	serie 581	Article number 99 2006 210 03

Item description

