

Product data sheet

Miniature connectors



Product description	Male panel mount connector, Contacts: 14 (14-b), unshielded, THT, IP67, front fastened
-	-
Area	M16 IP67 series 723
Part no.	09 0453 48 14

Technical data

General features

Part no.	09 0453 48 14
Connector design	Male panel mount connector
Type standard	DIN EN 61076-2-106
Connector locking system	screw
Termination	THT
Degree of protection	IP67
Temperature range from/to	-40 °C / 95 °C
Mechanical operation	> 500 Mating cycles
Weight (g)	13.10
Customs tariff number	85369010
Country of Origin	DE

Electrical parameters

Rated voltage	60 V
Rated impulse voltage	500 V
Rated current	3,0 A
Pollution degree	1
Overvoltage category	I
Insulating material group	III
EMC compliance	unshielded

Material

Contact body material	PBT (UL94 V-0)
Contact material	CuZn (brass)
Contact plating	Au (gold)
REACH SVHC	CAS 7439-92-1 (Lead)
SCIP number	4a234214-6dc0-4e3f-a766-fe7cdcf2692

Classifications

eCl@ss 11.1	27-44-01-09
ETIM 9.0	EC003569

Product data sheet

Miniature connectors



Product description	Male panel mount connector, Contacts: 14 (14-b), unshielded, THT, IP67, front fastened
-	-
Area	M16 IP67 series 723
Part no.	09 0453 48 14

General Disclaim Notice

The connectors have been developed for applications in plant engineering, control and electrical equipment construction. The user is responsible for checking whether the connectors can also be used in other areas of application.

Plug connectors with enclosure protection IP67 and IP68 are not suitable for use under water. When used outdoors, the plug connectors must be protected separately against corrosion. For further information on the IP protection classes, please refer to the "Technical Information" download centre.